



**BESLER**  
GLASS FIBER

**CC**

Assembled Roving for  
Centrifugal Casting Applications



## PRODUCT FEATURES

- Boron-free ECR-Glass
- Environment friendly
- Good unwinding
- Good wet out
- Good choppability
- Low fuzz & static

## PRODUCT SPECIFICATION

• Glass Type	ECR (B-Free)
• Roving Tex (g/10 <sup>3</sup> m)	2400 ± % 5
• Filament Diameter (μ)	Nom. 13
• Split Tex (g/10 <sup>3</sup> m)	Nom. 133
• Moisture Content (%)	Max. 0.1
• Sizing Type	Silane
• Loss of Ignition (%)	0,75 ±0,15
• Compatability	Polyester, Vinylester

## PACKAGING

Type	Pallet Dimensions (cm)	Bobbins per Pallet	Layers per Pallet	Pallet Height (cm)	Product Net Weight per Pallet
Bulk Packaging	93 x 123	48	4	120	1032

## BOBIN DIMENSION

weight (kg)	Inner diameter (mm)	outer diameter(mm)	height(mm)
Nom. 21,5	75	295	255

## STORAGE

Products should be stored in original package in dry and dust free area.  
Storage temperature is between 10°C - 30°C at humidity between 50% - 75%. Pallets must be single stacked.

## GUARANTEE

All physical & chemical properties represent average values and subject to normal production variations.  
The specifications are also subject to change. For current information please contact Beşler Office.



**BEŞLER TEKSTİL SANAYİ ve TİC. A.Ş.**

Address: Sultansazı Mh. 10. Cd. No:1 O.S.B. İncesu / Kayseri / TÜRKİYE M: +90 (535) 545 18 93 T: +90 (352) 504 06 02 (pbx)

[www.beslerglassfiber.com.tr](http://www.beslerglassfiber.com.tr)