



**BESLER**  
GLASS FIBER

**HL**

Assembled Roving for  
Head Liner Applications



## PRODUCT FEATURES

- Boron-free ECR-Glass
- Environment friendly
- Good unwinding
- Good wet out in PU
- Good choppability
- Low fuzz & static

## PRODUCT SPECIFICATION

• Glass Type	ECR (B-Free)
• Filament Diameter ( $\mu$ )	Nom. 13
• Roving Tex ( $g/10^3m$ )	2400 $\pm$ % 5
• Split Tex ( $g/10^3m$ )	Nom. 50
• Moisture Content (%)	Max. 0.1
• Sizing Type	Silane
• Loss of Ignition (%)	1,2 $\pm$ 0,2
• Compatability	Polyurethane

## PACKAGING

Type	Pallet Dimensions (cm)	Bobbins per Pallet	Layers per Pallet	Pallet Height (cm)	Product Net Weight per Pallet
Bulk packaging	93 x 123	48	4	120	1032

## BOBIN DIMENSION

Weight (kg)	Inner diameter (mm)	Outer Diameter(mm)	Height(mm)
Nom. 21,5	75	295	255

## STORAGE

Products should be stored in original package in dry and dust free area.  
Storage temperature is between 10°C - 30°C at humidity between 50% - 75%. Pallets must be single stacked.

## GUARANTEE

All physical & chemical properties represent average values and subject to normal production variations.  
The specifications are also subject to change. For current information please contact Beşler Office.



**BEŞLER TEKSTİL SANAYİ ve TİC. A.Ş.**

Address: Sultansazı Mh. 10. Cd. No:1 O.S.B. İncesu / Kayseri / TÜRKİYE M: +90 (535) 545 18 93 T: +90 (352) 504 06 02 (pbx)

[www.beslerglassfiber.com.tr](http://www.beslerglassfiber.com.tr)