

LFD-2400

Chopped Direct
Roving



PRODUCT FEATURES

- Boron-free ECR-glass
- Environment friendly
- Excellent mechanical properties
- Low discoloration performance
- Optimal strand integrity
- Improved flow
- Low fuzz
- Improved bulk density for less storage and handling costs

PRODUCT

SPECIFICATION

LFD-50

LFD-13

• Glass Type	ECR (B-Free)	ECR (B-Free)
• Filament Diameter (μ)	Nom. 17	Nom. 17
• Moisture Content (%)	Max 0.07	Max 0.07
• Sizing Type	Silane	Silane
• Loss of Ignition (%)	0,55 $\pm$ 0,15	0,55 $\pm$ 0,15
• Compatability	Epoxy, Polyester, Vinylester Resins	Epoxy, Polyester, Vinylester Resins
• Fibre Length (mm)	Nom. 48	Nom. 13

PACKAGING


Type	Pallet Dimensions (cm)	Pallet Height (cm)	Pallet Quantity	Net Weight per Pallet (kg)
Big bag	114 x 114	150 +/- 5	1	1000-1100

STORAGE

Products should be stored in original package in dry and dust free area. Storage temperature is between 10°C - 30°C at humidity between 50% - 75%.

WARRANTY

All physical & chemical properties represent average values and subject to normal production variations. The specifications are also subject to change. For current information please contact Beşler Office.



BESLER
GLASS FIBER