

TPP

Chopped Strands for
PP Reinforcement



PRODUCT FEATURES

- Boron-free ECR-glass
- Environment friendly
- Excellent mechanical properties
- Low discoloration performance
- Optimal strand integrity
- Improved flow
- Low fuzz
- Improved bulk density for less storage and handling costs

PRODUCT SPECIFICATION

TPP

| | |
|-------------------------------|-----------------|
| • Glass Type | ECR (B-Free) |
| • Filament Diameter (μ) | Nom. 13 |
| • Moisture Content (%) | Max. 0.07 |
| • Sizing Type | Silane |
| • Loss of Ignition (%) | 0,65 \pm 0,15 |
| • Compatability | Polypropylene |
| • Fibre Length (mm) | Nom. 4.5 - 6 |

PACKAGING


| Type | Pallet Dimensions (cm) | Pallet Height (cm) | Quantity Per Pallet | Net Weight Per Pallet (kg) |
|---------|------------------------|--------------------|---------------------|----------------------------|
| Big bag | 112x 112 | 120 +/-20 | 1 | 1050 +/- 100 |

STORAGE

Products should be stored in original package in dry and dust free area. Storage temperature is between 10°C - 30°C at humidity between 50% - 75%. Pallets must be single stacked.

GUARANTEE

All physical & chemical properties represent average values and subject to normal production variations. The specifications are also subject to change. For current information please contact Beşler Office.



BESLER
GLASS FIBER