

# TS

## Assembled Roving for Translucent Sheet Weaving Stitching



### PRODUCT FEATURES

- Boron-free ECR-Glass
- Environment friendly
- Good unwinding
- Fast wet out
- Good translucency
- Good choppability & dispersion
- Low fuzz & static

### PRODUCT SPECIFICATION

	TS-2400 Weaving	TS (2) - 2400 Translucent Sheet
• Glass Type	ECR (B-Free)	ECR (B-Free)
• Filament Diameter (μ)	Nom. 13	Nom. 13
• Roving Tex (g/10 <sup>3</sup> m)	2400 ± % 5	2400 ± % 5
• Split Tex (g/10 <sup>3</sup> m)	Nom. 33	Nom. 33
• Moisture Content (%)	Max. 0,1	Max. 0,1
• Sizing Type	Silane	Silane
• Loss of Ignition (%)	0,55±0,15	0,55±0,15
• Compatability	Polyester Vinilester	Polyester Epoxy

### PACKAGING

Type	Pallet Dimensions (cm)	Bobbins per Pallet	Layers per Pallet	Pallet Height (cm)	Product Net Weight per Pallet (kg)
Cardboard	93 x 123	48	4	120 +/-5	1032

### BOBBIN DIMENSIONS

Weight (kg)	Inner Diameter(mm)	Outer Diameter(mm)	Height(mm)
Nom. 21,5	75	295	255

### STORAGE

Products should be stored in original package in dry and dust free area. Storage temperature is between 10°C - 30°C at humidity between 50% - 75%.

### WARRANTY

All physical & chemical properties represent average values and subject to normal production variations. The specifications are also subject to change. For current information please contact Beşler Office.



**BESLER**  
GLASS FIBER